



Material Safety Data Sheet

DOW CHEMICAL INTERNATIONAL PVT. LTD.

Product name: VORANOL™ 8010G Polyol

Issue Date: 27.02.2017

Print Date: 11.09.2017

DOW CHEMICAL INTERNATIONAL PVT. LTD. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: VORANOL™ 8010G Polyol

Recommended use of the chemical and restrictions on use

Identified uses: Component(s) for the manufacture of urethane polymers. For industrial use.

COMPANY IDENTIFICATION

DOW CHEMICAL INTERNATIONAL PVT. LTD.
GODREJ IT PARK - P2, 1st FLOOR, BLOCK B, 02
LBS ROAD, GODREJ BUSINESS DISTRICT
PIROJSHANAGAR
400079 VIKHROLI, MUMBAI
INDIA

Customer Information Number:

(91) 22-6674-1500
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 91-22-6674-1800

Local Emergency Contact: 22-6674-1800

2. HAZARDS IDENTIFICATION

GHS Classification

This product is not hazardous per the Globally Harmonized System of Classification and Labelling (GHS).

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a substance.

Component	CASRN	Concentration
-----------	-------	---------------

Glycerol, propylene oxide,
ethylene oxide polymer

9082-00-2

> 99.0 %

4. FIRST AID MEASURES

Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water. Suitable emergency safety shower facility should be immediately available.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be available in work area.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: Do not use direct water stream. May spread fire.

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Refer to section 7, Handling, for additional precautionary measures. Keep unnecessary and unprotected personnel from entering the area. Spilled material may cause a slipping hazard. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Absorb with materials such as: Dirt. Sand. Sawdust. Collect in suitable and properly labeled containers. Wash the spill site with water. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes. Wash thoroughly after handling. This material is hygroscopic in nature. Product shipped/handled hot can cause thermal burns. Keep container closed. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

Conditions for safe storage: Protect from atmospheric moisture. Store in a dry place. Avoid prolonged exposure to heat and air. Store in the following material(s): Carbon steel. Stainless steel. Polypropylene. Polyethylene-lined container. Teflon. Glass-lined container. Aluminum. Plasite 3066 lined container. Plasite 3070 lined container. 316 stainless steel. See Section 10 for more specific information.

Storage stability

Storage temperature: **Storage Period:**

15 - 35 °C

24 Month

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Exposure limits have not been established for those substances listed in the composition, if any have been disclosed.

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent. When handling hot material: Use chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent. Wear a face-shield which allows use of chemical goggles, or wear a full-face respirator, to protect face and eyes when there is any likelihood of splashes.

Skin protection

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. If hands are cut or scratched, use gloves chemically resistant to this material even for brief exposures. Use gloves with insulation for thermal protection (EN 407), when needed. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing. When handling hot material, protect skin from thermal burns. Selection of specific items will depend on the operation.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if material is heated or sprayed, use an approved air-purifying respirator. Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	liquid
Color	clear
Odor	mild
Odor Threshold	No test data available
pH	No test data available
Melting point/range	Not applicable
Freezing point	-27.8 °C <i>ASTM D97</i>
Boiling point (760 mmHg)	<i>Literature</i> Decomposes before boiling
Flash point	closed cup 221 °C <i>ASTM D 93</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Not Applicable
Lower explosion limit	No test data available
Upper explosion limit	No test data available
Vapor Pressure	Expected to be low
Relative Vapor Density (air = 1)	<i>Literature</i> >Air
Relative Density (water = 1)	1.0155 at 25 °C / 25 °C <i>Literature</i>
Water solubility	<i>Literature</i> negligible
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	<i>No test data available</i>
Decomposition temperature	No data available
Kinematic Viscosity	550 - 650 cSt at 25 °C <i>ASTM D4878</i>
Explosive properties	Not explosive
Oxidizing properties	No
Molecular weight	No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: Stable under recommended storage conditions. See Storage, Section 7.

Possibility of hazardous reactions: Will not occur by itself.

Conditions to avoid: Product can oxidize at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems.

Incompatible materials: Avoid contact with oxidizing materials. Avoid contact with: Strong acids. Strong bases. Avoid unintended contact with isocyanates. The reaction of polyols and isocyanates generates heat.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Carbon dioxide. Alcohols. Ethers. Hydrocarbons. Ketones. Polymer fragments.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

Single dose oral LD50 has not been determined.

Typical for this family of materials.

LD50, Rat, > 2,000 mg/kg Estimated. No deaths occurred at this concentration.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

The dermal LD50 has not been determined.

Typical for this family of materials.

LD50, Rabbit, > 2,000 mg/kg Estimated. No deaths occurred at this concentration.

Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. Vapor from heated material or mist may cause respiratory irritation.

For narcotic effects: No relevant data found.

The LC50 has not been determined.,

Skin corrosion/irritation

Prolonged exposure not likely to cause significant skin irritation.
May cause more severe response if skin is abraded (scratched or cut).
Material may be handled at elevated temperatures; contact with heated material may cause thermal burns.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.
May cause slight temporary corneal injury.

Sensitization

For this family of materials, sensitization studies done in guinea pigs have been negative.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

No relevant data found.

Carcinogenicity

No relevant data found.

Teratogenicity

No relevant data found.

Reproductive toxicity

No relevant data found.

Mutagenicity

One material tested in this family was negative in the Ames test.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Ecotoxicity

Acute toxicity to fish

For this family of materials:

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Persistence and degradability

Biodegradability: For this family of materials: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

Bioaccumulative potential

Bioaccumulation: For this family of materials: No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000).

Mobility in Soil

No data available.

Results of PBT and vPvB assessment

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Other adverse effects

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

13. DISPOSAL CONSIDERATIONS

Disposal methods: Any disposal practice must be in compliance with all local and national laws and regulations. Do not dump into any sewers, on the ground, or into any body of water.

14. TRANSPORT INFORMATION

Classification for ROAD and Rail transport:

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

**Transport in bulk
according to Annex I or II
of MARPOL 73/78 and the
IBC or IGC Code**

Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

This product has been classified in accordance with the criteria of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS), rev. 6.

16. OTHER INFORMATION

Revision

Identification Number: 101294799 / A146 / Issue Date: 27.02.2017 / Version: 3.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

DOW CHEMICAL INTERNATIONAL PVT. LTD. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.